

The hand held or bench mounted Bondwand employs a built-in, variable exposure timer of one, two, and three minute intervals as well as continuous. The Bondwand delivers 10mW/cm<sup>2</sup> of Ultra-violet light at 350nm or Visible light at 450nm and is an ideal tool for research applications, shop repair and a effective NDT board inspection system when used with an available Black Light Lamp.

## BONDWAND UV CURING SYSTEM

### Sample Applications:

- Field Service Repair
- On-Line Repair
- Research & Development
- Board Inspection
- PC Board Repair
- Small Device Repair



### Specifications:

UV Output: 10 mW/cm<sup>2</sup> @ 350nm  
Input Power: 120VAC/60Hz  
Exposure Area: 5' x 1 3/4"  
Timer: 1, 2 and 3 minutes  
Dimensions: 2 1/2"W x 12 7/8"H x 1 5/8"D  
Weight: 1 lb, 8 oz.

### \* Ordering Information:

81002 Bondwand 350nm 120V/60Hz  
81024 Bondwand 450nm 120V/60Hz  
81485 Fluor-Tek NDT-BL 120V/60Hz  
82469 350nm replacement lamp  
82470 450nm replacement lamp  
80765 Solid UV protective shield

### Features:

Swivel table mount for ease of use, variable exposure times of one, two or three minutes as well as continuous. Light in weight yet solid in constructions allows ergonomic use while resisting harsh environments.



6 Trowbridge Drive  
Bethel CT 06801  
Phone: 203-743-4059  
Fax: 203-743-6733  
[www.electro-lite.com](http://www.electro-lite.com)